

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.		FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.		
10/735,311		12/12/2003	William Andrew Hennessy	133458	2242		
41838	7590	09/22/2005		EXAMINER			
GENERAL	L ELECT	TRIC COMPANY (	PCPI)	WATSON, KRISTIE D			
C/O FLETC P. O. BOX (		DER		ART UNIT	PAPER NUMBER		
HOUSTON		269-2289		2878			
				DATE MAILED: 09/22/200	5		

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)	
Office Anti-us Comments	10/735,311	HENNESSY ET AL.	
Office Action Summary	Examiner	Art Unit	
	Kristie Watson	2878	
The MAILING DATE of this communication Period for Reply	on appears on the cover sheet wi	th the correspondence addr	ess
A SHORTENED STATUTORY PERIOD FOR F WHICHEVER IS LONGER, FROM THE MAILIN  - Extensions of time may be available under the provisions of 37 of after SIX (6) MONTHS from the mailing date of this communicati  - If NO period for reply is specified above, the maximum statutory  - Failure to reply within the set or extended period for reply will, by Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	NG DATE OF THIS COMMUNIC CFR 1.136(a). In no event, however, may a re- on. period will apply and will expire SIX (6) MON statute, cause the application to become AB	CATION.  eply be timely filed  THS from the mailing date of this company (35 U.S.C. § 133).	
Status			
1) Responsive to communication(s) filed on	21 December 2003		
· <u> </u>	This action is non-final.		
3) Since this application is in condition for a		ers, prosecution as to the r	nerits is
closed in accordance with the practice ur	·	* *	,
Disposition of Claims	, , , ,		
4)⊠ Claim(s) <u>1-30</u> is/are pending in the applic	ation		
4a) Of the above claim(s) is/are with			
5) Claim(s) is/are allowed.			
6)⊠ Claim(s) <u>1-30</u> is/are rejected.			
7) Claim(s) is/are objected to.			
8) Claim(s) are subject to restriction a	and/or election requirement.		
Application Papers			
9) The specification is objected to by the Exa	aminer		
10)⊠ The drawing(s) filed on <u>31 December 200</u>		objected to by the Examin	er.
Applicant may not request that any objection t		-	
Replacement drawing sheet(s) including the c			1.121(d).
11) The oath or declaration is objected to by t	· -	· · · · · · · · · · · · · · · · · · ·	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for fo	reign priority under 35 H.S.C. &	119(a) <sub>-</sub> (d) or (f)	
a) ☐ All b) ☐ Some * c) ☐ None of:	reign priority under 55 0.5.6. §	119(a)-(a) or (i).	
1.☐ Certified copies of the priority docu	ments have been received		
2. Certified copies of the priority docu		oplication No	
3. Copies of the certified copies of the	·	· ·	age
application from the International B	•		9-
* See the attached detailed Office action for	, , , , , , , , , , , , , , , , , , , ,	received.	
	•		
Attachment(s)			
Notice of References Cited (PTO-892)	4) Interview S	ummary (PTO-413)	
<ul> <li>P)</li></ul>		)/Mail Date formal Patent Application (PTO-1	52)
Paper No(s)/Mail Date <u>12/03</u> .	6) Other:	• •	
Patent and Trademark Office			

Art Unit: 2878

### **DETAILED ACTION**

## Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(a) the invention was known or used by others in this country, or patented or described in a printed publication in this or a foreign country, before the invention thereof by the applicant for a patent.

- 2. Claim 1-7, 9-12, 14, 16-19, 22, 24-27, and 29 are rejected under 35 U.S.C. 102 a) as being anticipated by Sato et al. U. S. Patent Number 6,573, 506 B2.
- 3. Pertaining to claim 1, **Sato et al**. (Column 1, Lines 55-62 and Column 4, Lines 30-35) discloses that a radiation detector assembly (Figure 1) comprising: a detector substrate;

a detector matrix array disposed on said detector substrate;


a scintillator material (12) disposed on said detector matrix array;

a moisture resistant layer disposed on said scintillator material (12), said moisture resistant layer comprising a plurality of sub-layers, a protective cover (10a) disposed over said detector substrate and said moisture resistant layer (16);

and an adhesive material disposed between said detector substrate and said cover; wherein said adhesive material is disposed so that it is not in contact with said moisture resistant layer. See Figure 1 Sato et al.

Art Unit: 2878

Fig.1



- 4. Pertaining to claim 2, **Sato et al**. (Column 2 Lines 63-65) discloses that a detector assembly in accordance with Claim 1, wherein said moisture resistant layer further comprises an encapsulating coating disposed on said scintillator material and a reflective sub-layer disposed on said encapsulating coating.
- 5. Pertaining to claim 3, **Sato et al.** (Column 4, Lines 30-40 and 45-47) discloses that a detector assembly in accordance with Claim 2, wherein said moisture resistant layer further comprising one or more; moisture resistant sub-layers disposed on said reflective layer, said one or more moisture resistant sub-layers being substantially transparent to a radiation to be detected by said detector assembly.
- 6. Pertaining to claim 4, **Sato et al**. (Column 5, Lines 65-67 and Column 6, Lines 1-5) discloses that a detector assembly in accordance with Claim 3, wherein said plurality

Art Unit: 2878

of sub-layers are selected from a group consisting of titanium, aluminum, nickel, a polymer comprising one or more types of substituted or unsubstituted para-xylylene materials, magnesium fluoride (MgF<sub>2</sub>), silicon oxide (SiO), aluminum fluoride (AlF<sub>3</sub>), silicon dioxide (SiO<sub>2</sub>), titanium dioxide (TiO<sub>2</sub>), a silicone potting compound and combinations thereof.

- 7. Pertaining to claim 5, **Sato et al**. (Column 5, Lines 65-67 and Column 6, Lines 1-5) discloses that a detector assembly in accordance with Claim 2, wherein said encapsulating coating comprises a material selected from a group consisting of magnesium fluoride (MgF<sub>2</sub>), silicon oxide (SiO), aluminum fluoride (AlF<sub>3</sub>), titanium dioxide (TiO<sub>2</sub>), silicon dioxide (SiO<sub>2</sub>), a polymer comprising one or more layers of substituted or unsubstituted para-xylylene materials, and combinations thereof.
- 8. Pertaining to claim 6, **Sato et al**. (Column 5, Lines 12-15) in view of **Kingsley et al**. (Column 4, Lines 10-31) discloses that a detector assembly in accordance with Claim 2, wherein said reflective layer is selected from a group consisting of silver, gold, aluminum, a polyester film with a layer of pressure sensitive adhesive, and combinations thereof.
- 9. Pertaining to claim 7, **Sato et al.** (Column 5, Lines 40-45) discloses that a detector assembly in accordance with Claim 1 wherein said protective cover comprises graphite.

Art Unit: 2878

- 10. Pertaining to claim 9, **Sato et al.** (Column 2, Lines 1-7, and Column 1 Lines 55-66) discloses that an X-ray detector assembly comprising: a detector substrate; a detector matrix array disposed on said detector substrate; an X-ray scintillator material disposed on said detector matrix array; a moisture resistant layer disposed on said scintillator material (12), said moisture resistant layer comprising a plurality of sub-layers,a protective cover (10a) disposed over said detector substrate and said moisture resistant layer; and an adhesive material disposed between said detector substrate and said cover; wherein said adhesive material is disposed so that it is not in contact with said moisture resistant layer(16).
- 11. Pertaining to claim 10, **Sato et al**. (Column 5, Lines 1-10 and Column 8, Lines 11-15) discloses that an X-ray detector assembly in accordance with Claim 9 wherein said moisture resistant layer further comprises an encapsulating coating layer disposed on said scintillator material and a reflective sub-layer disposed on said encapsulating coating layer.
- 12. Pertaining to claim 11, **Sato et al.** (Column 3, Lines 42-65 and Column 4 Lines 30-40) discloses that an X-ray detector assembly in accordance with Claim 10 said moisture resistant layer further comprising one or more moisture resistant sub-layers

Art Unit: 2878

disposed on said reflective layer, said one or more moisture resistant sub-layers being substantially transparent to X-rays.

- 13. Pertaining to claim 12, **Sato et al**. (Column 5, Lines 40-45) discloses that an X-ray detector assembly in accordance with Claim 9 wherein said protective cover comprises graphite.
- 14. Pertaining to claim 14, **Sato et al.** (Column 6, Lines 1-5) discloses that an X-ray detector assembly in accordance with Claim 9 wherein said X-ray scintillator is selected from the list consisting of cesium iodide (CsI), CSI (TI), CsI (Na), NaI (TI), LiI (Eu), and combinations thereof.
- 15. Pertaining to claim 16, **Sato et al.** (Column 6, Lines 20-40) discloses that a radiation detector assembly comprising: a detector substrate;
- a detector matrix array disposed on said detector substrate;
- a contact finger area disposed on said detector substrate and in electrical communication (80) with said detector matrix array (20);
- a scintillator material (12) disposed on said detector matrix array (20);
- a moisture resistant layer disposed on said scintillator material, said moisture resistant layer comprising a plurality of sub-layers; and a protective cover (10a)disposed over said detector substrate and said moisture resistant layer (16);

Art Unit: 2878

wherein said protective cover is bonded to said moisture resistant layer using an adhesive material; and wherein said moisture resistant layer is disposed so that an edge portion of said moisture resistant layer is bonded to said detector substrate between said adhesive material and said contact finger area. See Figure 1, Sato et al.

- 16. Pertaining to claim 17, **Sato et al.** (Column 5, Lines 5-10) discloses that a radiation detector assembly in accordance with Claim 16, wherein said moisture resistant layer further comprises an encapsulating coating layer disposed on said scintillator material and a reflective sub-layer disposed on said encapsulating coating layer.
- 17. Pertaining to claim 18, **Sato et al**. (Column 6, Lines 1-5) discloses that a radiation detector assembly in accordance with Claim 17, wherein said plurality of sublayers are selected from a group consisting of titanium, aluminum, nickel, a polymer comprising one or more types of substituted or unsubstituted paraxylylene materials, magnesium fluoride (MgF<sub>2</sub>) silicon oxide (SiO), aluminum fluoride (AlF<sub>3</sub>), silicon dioxide (SiO<sub>2</sub>), titanium dioxide (TiO<sub>2</sub>), a silicone potting compound, and combinations thereof.
- **18.** Pertaining to claim 19, **Sato et al**. (Column 1, Lines 55-60 and Column 2, Lines 63-65, Column 4, Lines 30-35) discloses that a radiation detector assembly in accordance with Claim 17, wherein said moisture resistant layer further comprises one

Art Unit: 2878

or more moisture resistant sub-layers disposed on said reflective layer, said one or more moisture resistant sub-layers being substantially transparent to X-rays.

- 19. Pertaining to claim 22, **Sato et al**. (Column 5, Lines 40-45) discloses that a detector assembly in accordance with Claim 16 wherein said protective cover comprises graphite.
- 20. Pertaining to claim 24, **Sato et al.** (Column 1, Lines 55-66, Column 2, Lines 1-7, and Column 4, Lines 30-35) discloses that an X-ray detector assembly comprising: a detector substrate;

a detector matrix array disposed on said detector substrate;

a contact finger area disposed on said detector substrate and in electrical communication (80) with said detector matrix array (20);

an X-ray scintillator material disposed on said detector matrix array (20);

a moisture resistant layer disposed on said scintillator material, said moisture resistant layer comprising a plurality of sub-layers;

and a protective cover disposed over said detector substrate and said moisture resistant layer (16);

wherein said protective cover is bonded to said moisture resistant layer using an adhesive material;

Art Unit: 2878

and wherein said moisture resistant layer is disposed so that an edge portion of said moisture resistant layer is bonded to said detector substrate between said adhesive material and said contact finger area. See **Figure 1 Sato et al.** 

- 21. Pertaining to claim 25, **Sato et al.** (Column 2 Lines 63-65) discloses that an X-ray detector assembly in accordance with Claim 24 wherein said moisture resistant layer further comprises an encapsulating coating layer disposed on said scintillator material and a reflective sub-layer disposed on said encapsulating coating layer.
- 22. Pertaining to claim 26, **Sato et al.** (Column 3, Lines 42-65 and Column 4 Lines 30-40) discloses that an X-ray detector assembly in accordance with Claim 25 said moisture resistant layer further comprising one or more moisture resistant sub-layers disposed on said reflective layer, said one or more moisture resistant sub-layers being substantially transparent to X-rays.
- **23.** Pertaining to claim 27, **Sato et al.** (Column 7, Lines 50-55) discloses that an X-ray detector assembly in accordance with Claim 24 wherein said protective cover comprises graphite.
- 24. Pertaining to claim 29, **Sato et al.** (Column 6, Lines 1-5) discloses that an X-ray detector assembly in accordance with Claim 24 wherein said X-ray scintillator material is selected from the list consisting of cesium iodide (CsI) CSI(TI), CsI(Na), NaI(TI), LiI(I:u), and combinations thereof.

Art Unit: 2878

### Claim Rejections - 35 USC § 103

- 25. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 26. Claims 8, 13,23, and 28 are rejected under 35 U.S.C. 103(a) as being obvious over Sato et al. U. S. Patent Number 6,573, 506 B2 in view of Suzuki et al. U.S. Publication Number 2005/0156113 A1.
- 27. Pertaining to claim 8, **Suzuki et al.** (033) discloses that a detector assembly in accordance with Claim 1, wherein said protective cover comprises plastic.
- 28. Pertaining to claim 13, **Suzuki et al.** (0033) discloses that an X-ray detector assembly in accordance with Claim 9 wherein said protective cover comprises plastic.
- 29. Pertaining to claim 23, **Suzuki et al**. (0033) discloses that a detector assembly in accordance with Claim 16 wherein said protective cover comprises plastic.


Art Unit: 2878

30. Pertaining to claim 28, **Suzuki et al.** (0033) discloses that an X-ray detector assembly in accordance with Claim 24 wherein said protective cover comprises plastic.

- 31. Claims 15, 20, 21, and 30 are rejected under 35 U.S.C. 103(a) as being obvious over Sato et al. U. S. Patent Number 6,573, 506 B2 in view of Kingsley et al. U.S Patent Number 5,179, 284.
- 32. Sato et al. discloses the limitations as claimed except he does not teach that the protective covering is made of plastic and that the scintillator is comprised of cesium iodide needles. However, Kingsley et al. does teach that the scintillator is comprised of cesium iodide needles. Suzuki et al. teaches the concept of the protective covering made of plastic. Therefore it would have been obvious to one that is skilled in the art to combine the limitations of the scintillator as claimed by Sato et al. with Kingsley et al.'s cesium iodide needles in order to design a scintillator that maximizes its imaging efficiency by preventing the build-up of the moisture on the scintillator material. It also would have been obvious to combine Sato et al. and Kingsley et al. inventions with Suzuki et al.'s protective covering made of plastic to ensure the durability of the construction of the radiation detector assembly.

See FIGS. 3-12, where Sato et al. teaches the claimed limitations. See Kingsley et al. Figure 1.

Art Unit: 2878



- 33. Pertaining to claim 15, **Kingsley et al.** (Column 1, Lines 31-46) discloses that an X-ray detector assembly in accordance with Claim 9 wherein said X-ray scintillator comprises cesium iodide (CsI) needles.
- 34. Pertaining to claim 20, **Sato et al.** (Column 6, Lines 1-5) in view of **Kingsley et al.** (Column 4, Lines 10-31) discloses that a radiation detector assembly in accordance with Claim 17, wherein said encapsulating coating layer is selected from a group consisting of magnesium fluoride (MgF<sub>2</sub>), silicon oxide aluminum fluoride (AlF<sub>3</sub>), Titanium dioxide(TiO<sub>2</sub>), silicon dioxide (SiO<sub>2</sub>), a polymer comprising one or more tiers of substituted or unsubstituted para-xylylene materials, and combinations thereof.

Art Unit: 2878

35. Pertaining to claim 21, **Sato et al.** (Column 5, Line 12-15) in view of **Kingsley et al.** (Column 4, Lines 10-31) discloses that a radiation detector assembly as in claim 17, wherein said reflective layer is selected from a group consisting of silver, gold, aluminum, a polyester film with a layer of pressure sensitive adhesive, and combinations thereof.

36. Pertaining to claim 30, **Kingsley et al.** (Column 1, Lines 31-46) discloses that an X-ray detector assembly in accordance with Claim 24 wherein said X-ray scintillator material comprises cesium iodide (Csl) needles.

#### Conclusion

37. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kristie Watson whose telephone number is (571) 272-5052. The examiner can normally be reached on 8:00 am - 4:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Porta can be reached on (571) 272- 2444. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2878

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Kristie Watson Patent Examiner Art Unit 2878

DAVID PORTA
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2800